

MATERIAL SAFETY DATA SHEET

This MSDS complies with OSHA'S Hazard Communication Standard 29 CFR 1910.1200 and OSHA Form 174

IDENTITY AND MANUFACTURER'S INFORMATION	
NFPA Rating: Health-1; Flammability-1; Reactivity-0; Special-- Manufacturer's Name: AMREP, INC. Address: 990 Industrial Park Drive Marietta, GA 30062 Date Prepared: 03/10/05 Prepared By: IB/TR Information Calls: (770)422-2071 EMERGENCY RESPONSE NUMBER: 1(800)255-3924	HMIS Rating: Health-1; Flammability-1; Reactivity-0; Personal Protection-B DOT Hazard Classification: ORM-D Identity (trade name as used on label): MISTY WATER BASED CHALKBOARD AND WHITEBOARD CLEANER MSDS Number: A00101 Revision: 16 NOTICE: JUDGEMENT BASED ON INDIRECT TEST DATA

SECTION 1 - MATERIAL IDENTIFICATION AND INFORMATION					
COMPONENTS-CHEMICAL NAMES AND COMMON NAMES <small>(Hazardous Components 1% or greater; Carcinogens 0.1% or greater)</small>	CAS Number	SARA III LIST	OSHA PEL (ppm)	ACGIH TLV (ppm)	Carcinogen Ref. Source **
2-BUTOXYETHANOL*	111-76-2	Yes*	25 (skin)	20 (skin)	d
ETHANOL	64-17-5	No	1000	1000	d
ISOBUTANE / PROPANE BLEND	75-28-5	No	800	800	d
	74-98-6	No	1000	1000	d
*GLYCOL ETHER					

SECTION 2 - PHYSICAL/CHEMICAL CHARACTERISTICS	
Boiling Point: N/A	Specific Gravity (H2O=1): Concentrate Only =0.985
Vapor Pressure: PSIG @ 70°F (Aerosols): Max.70	Vapor Pressure (Non-Aerosols)(mm Hg and Temperature): N/A
Vapor Density (Air = 1): N/E	Evaporation Rate (= 1): N/E
Solubility in Water: Soluble	Water Reactive: No
Appearance and Odor: White foam, sassafras fragrance.	

SECTION 3 - FIRE AND EXPLOSION HAZARD DATA		
FLAMMABILITY as per USA FLAME PROJECTION TEST (aerosols) NON-FLAMMABLE	Auto Ignition Temperature N/E	Flammability Limits in Air by % in Volume: % LEL: N/E % UEL: N/E
FLASH POINT AND METHOD USED (non-aerosols): N/A		EXTINGUISHER MEDIA: Foam, dry chemical, carbon dioxide.
SPECIAL FIRE FIGHTING PROCEDURES: Self-contained breathing apparatus.		
Unusual Fire & Explosion Hazards: Do not expose aerosols to temperatures above 130°F or the container may rupture.		

SECTION 4 - REACTIVITY HAZARD DATA	
STABILITY [X] STABLE [] UNSTABLE Incompatibility (Mat. to avoid): Strong oxidizers.	HAZARDOUS POLYMERIZATION [] WILL [X] WILL NOT OCCUR Conditions to Avoid: Open flame, welding arcs, heat, sparks.
Hazardous Decomposition Products: Carbon monoxide, carbon dioxide.	

SECTION 5 - HEALTH HAZARD DATA	
PRIMARY ROUTES OF ENTRY: [X] INHALATION [] INGESTION [X] SKIN ABSORPTION [] EYE [] NOT HAZARDOUS	

ACUTE EFFECTS:	
Inhalation: Excessive inhalation of vapors can be harmful & may cause headache, dizziness, asphyxia, anesthetic effects & possible unconsciousness.	
Eye Contact: Slight irritation.	Skin Contact: Slight irritation.
Ingestion: Possible chemical pneumonitis if aspirated into lungs.	
CHRONIC EFFECTS: None known to humans. Note: some animal data indicates some reports of anemia, liver, kidney, lung, blood damage when excessively exposed to 2-butoxyethanol.	
Medical Conditions Generally Aggravated by Exposure: May aggravate existing eye, skin, or upper respiratory conditions.	

EMERGENCY FIRST AID PROCEDURES	
Eye Contact: Flush with water for 15 minutes. If irritated, seek medical attention.	
Skin Contact: Wash with soap and water. If irritated, seek medical attention.	
Inhalation: Remove to fresh air. Resuscitate if necessary. Get medical attention.	
Ingestion: DO NOT INDUCE VOMITING. Drink two large glasses of water. Get immediate medical attention.	

SECTION 6 - CONTROL AND PROTECTIVE MEASURES	
Respiratory Protection (specify type): If vapor concentration exceeds TLV, use respirator approved by NIOSH / MSHA for organic vapors.	
Protective Gloves: Disposable latex gloves suggested.	Eye Protection: Safety glasses recommended.
Ventilation Requirements: Adequate ventilation to keep vapor concentration below TLV.	
Other Protective Clothing & Equipment: None	
Hygienic Work Practices: Wash with soap and water before handling food. Remove contaminated clothing.	

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE	
Steps To Be Taken If Material Is Spilled Or Released: Absorb with suitable medium. Incinerate or landfill according to local, state or Federal regulations. Dilute with water and flush to sewer.	
Waste Disposal Methods: Aerosol cans when vented to atmospheric pressure through normal use, pose no disposal hazard.	
Precautions To Be Taken In Handling & Storage: Do not puncture or incinerate containers. Do not store at temperatures above 130°F.	
Other Precautions &/or Special Hazards: KEEP OUT OF REACH OF CHILDREN. Avoid food contamination. Avoid breathing vapors.	

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind.

** Chemical Listed as Carcinogen or Potential Carcinogen. [a] NTP [b] IARC Monograph [c] OSHA [d] Not Listed [e] Animal Data Only