

MATERIAL SAFETY DATA SHEET

ARCOT Manufacturing Corporation
2950 Mowery Road
Houston, Texas 77045-4809

Emergency Telephone:
(713) 413-9700
Date Prepared: 10/20/2008

SECTION I				
Product Identity (Name / Number)		OVEN CLEAN Oven & Grill Cleaner / 9684		
Chemical Family		Alkaline Cleaner. Corrosive liquids, n.o.s. (contains Sodium hydroxide solution), 8, UN1760, PGII, CORROSIVE.		
SECTION II - Hazardous Ingredients				
Hazardous Components	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
Sodium Hydroxide	2 mg/m ³	2 mg/m ³		Proprietary
Disodium Trioxosilicate Pentahydrate	15 mg/m ³	10 mg/m ³		Proprietary
Ethylene Glycol Monobutyl Ether	25ppm	25ppm		Proprietary
Methanol	200ppm	200ppm		< 1%
SECTION III - Physical & Chemical Characteristics				
Boiling Point		Specific Gravity		1.2
Above 212°F		Melting Point		N/A
Vapor Pressure (mm Hg)		Evaporation Rate (Ethyl Ether=1)		Less than 1
N/A		Appearance / Odor		Colorless Liquid / No Odor
pH				
13				
Solubility in Water				
Complete				
SECTION IV - Fire & Explosion Hazard Data				
Flammable Limits (Explosive Limit)		Upper: N/A	Lower: N/A	
Flash Point (Method Used)		N/A		
Extinguishing Media		Material is nonflammable. Water spray, foam, carbon dioxide, or dry chemical may be used for surrounding fires.		
Special Fire Fighting Procedures		Product is not flammable. Wear full protective clothing.		
Unusual Fire and Explosion Hazards		Avoid contact with aluminum, zinc, tin and their alloys since product reacts with these metals generating hydrogen gas which is flammable and/or explosive when ignited. Do not mix with strong acids to prevent violent or explosive reaction.		
SECTION V - Reactivity Data				
Stability:		Unstable	X	Stable
Hazardous Polymerization:		X	Will Not Occur	
Conditions To Avoid		Excessive heat. See Special Precautions.		
Incompatibility (Materials to Avoid)		Strong acids; also see Section IV. Avoid contact with water, metals, leather, wool, organic halogen compounds and organic nitro compounds.		
Hazardous Decomposition or Byproducts		Reacts with aluminum, zinc and their alloys generating hydrogen gas which is flammable and/or explosive when ignited.		

SECTION VI(a) - Health Hazard Data			
Inhalation	CORROSIVE. Breathing mists may cause damage to nasal and respiratory passages.		
Eye	Highly CORROSIVE. Even slight contact of the liquid with eyes will result in irritation and severe burns.		
Skin	Product is corrosive and will cause skin burns. Treat immediately.		
Ingestion	Swallowing will result in severe damage to mucous membranes. Ingestion may cause intense pain, nausea, vomiting and collapsing. Contains methanol which may cause blindness.		
Reported As Potential Carcinogen or Carcinogen			
	International Agency for Research on Cancer	X	Not Applicable
	National Toxicology Program		OSHA
SECTION VI(b) - First Aid Procedures			
Inhalation	Remove victim to fresh air. If breathing is difficult, administer oxygen. If not breathing, perform artificial respiration. Get medical attention.		
Eye	Immediately flush eyes with plenty of water for at least 15 minutes, while holding eyelids open. Get medical attention.		
Skin	Wash thoroughly with water for at least 15 minutes. Remove contaminated clothing. Get medical attention.		
Ingestion	If conscious and alert, give large quantities of water. Induce vomiting. Get medical attention.		
SECTION VI(c) - Employee Protection			
Respiratory Protection (Utilize NIOSH approved respirators. Refer to manufacturer's protection factors and OSHA standard 1910.134 as a guideline.) CORROSIVE. If TLV of product is exceeded, use NIOSH approved respirator, fully enclosed.			
<u>SPECIAL PROTECTION INFORMATION:</u>			
EYE	Chemical safety goggles or full face shield required.		
SKIN	Chemical resistant gloves required, natural and butyl rubber gloves suggested.		
VENTILATION	Provide sufficient mechanical ventilation to maintain exposure below TLV's.		
SPECIAL PROTECTION	Impervious clothing and boots may be worn to prevent skin contact. Showers and eyewash facilities should be in close proximity.		
SECTION VII - Special Precautions			
Handling and Storage	Store in dry, cool area. Excessive heat may cause pressure build-up. Avoid contact with metals, organic halogen compounds and nitro compounds. Do not store with strong acids. Keep container closed.		
Other Precautions	Addition of water releases heat which may result in boiling or splattering. Always add small amounts of material to water. Do not add water to material.		
SECTION VIII - Environmental Protection			
Spills / Releases	Trained personnel wearing protective equipment should contain spill. Neutralize with dilute acid. Scoop up and wash site. Notify authorities for spills of 1,000 Lb. or more.		
Waste Disposal Method	Neutralize alkalinity with sodium bicarbonate or dilute acid. Dispose of in accordance with applicable local, state and federal regulations.		

DISCLAIMER

The information contained herein is based upon data available to us and reflects our best professional judgment. Since it is impossible to anticipate the conditions under which our products may be used, we cannot guarantee that the recommendations will be adequate for all individuals and situations. Each user of this product should determine the suitability of the product for his particular purpose and should comply with all federal, state and local regulations. Our goal is to manufacture products with zero or minimal hazards. Our products are improved daily as up-to-date information and research is received from our suppliers to use products with less or no hazards. Please feel free to contact us for current information.