

\*\*\*\*\* MATERIAL SAFETY DATA SHEET \*\*\*\*\*

**"WOOD GLO "**  
**Premium Wood Floor Cleaner**

SUNBELT LABORATORIES P.O. BOX 1563 STAFFORD, TEXAS 77497 (281) 261-4747  
\*\*\*\*\*

EMERGENCY ASSISTANCE

For emergency assistance involving chemicals call CHEM TEL (800) 255-3924  
\*\*\*\*\*

PRODUCT IDENTIFICATION

PRODUCT NAME: **WOOD GLO** DATE PREPARED: 02-10-10  
IDENTITY: **PREMIUM WOOD FLOOR CLEANER** DATE REVISED:  
CHEMICAL FAMILY: ORGANIC CLEANER MSDS NO: 3210 REV. NO:  
\*\*\*\*\*

HAZARDOUS INGREDIENTS

MATERIAL	CAS #	OSHA PEL	AGCIH TLV	Approx %
D-Limonene	5989-27-05	NOT LISTED	NOT LISTED	

HAZARD RATINGS:

Health: 1

Fire: 0

Reactivity: 1 Special: none

HAZARD RATING SCALE:

0=Minimal

3=Serious

1=Slight

4=Severe

2=Moderate

\*\*\*\*\*

PHYSICAL DATA

BOILING POINT, @ 760 mm Hg > 212 F SOLUBILITY IN WATER 100 %  
SPECIFIC GRAVITY @ 77 F 1.002 VAPOR PRESSURE, mm Hg @ 77 F < 1  
VAPOR DENSITY, (AIR=1) > 1 VOLATILES, BY VOLUME > 95 %  
APPEARANCE @ 77F CLEAR YELLOW LIQUID ODOR ORANGE PEEL  
pH (100 %) 7.3 MELTING POINT < 32 F  
\*\*\*\*\*

FIRE AND EXPLOSION HAZARD DATA

FLASH POINT, TOC: None to Boil. FLAMMABLE LIMITS IN AIR, % BY VOLUME:  
Unknown LOWER: Undetermined UPPER: Undetermined. EXTINGUISHING MEDIA:  
Use Carbon Dioxide or Dry Chemical on small fires. Use foam (alcohol,  
polymer or ordinary) and water spray for large fires. SPECIAL FIRE  
FIGHTING PROCEDURES: Self-contained breathing apparatus and protective  
clothing should be worn in fighting fires involving chemicals. UNUSUAL  
FIRE & EXPLOSION HAZARDS: None known to Sunbelt Laboratories.  
\*\*\*\*\*

HEALTH HAZARD DATA

PRIMARY ROUTES OF EXPOSURE: Eye or Skin contact, Ingestion & Inhalation.  
SIGNS AND SYMPTOMS OF EXPOSURE: ACUTE: EYES: A burning irritation. SKIN:  
None, except if contact is made with an open wound. INGESTION: Immediate  
burning of all tissues contacted by the liquid. Production of  
gastrointestinal gas. INHALATION: Immediate burning of all tissue  
contacted by the liquid. CHRONIC: EYES: Could cause permanent damage.  
SKIN: Can cause an irritation. INGESTION: Reaction with digestive juices  
in the stomach will produce gas production. Burping or hiccups will  
result. INHALATION: Can cause irritation of the tissues affected in the  
respiratory tract. CARCINOGENICITY: this product is non-carcinogenic.  
SIGNS AND SYMPTOMS OF OVEREXPOSEURE: EYES: Extreme burning of the eyes  
tissues. SKIN: Liquid that touches the skin will be slightly

\*\*\*\*\* MATERIAL SAFETY DATA SHEET \*\*\*\*\*

**"WOOD GLO "**

**Premium Wood Floor Cleaner**

slick. Repeated contact will produce a rash. INGESTION: A possible build up of gastrointestinal gas, hiccups, burping. INHALATION: Irritation of the respiratory tract tissues contacted. EMERGENCY AND FIRST AID PROCEDURES: EYES: Flush with water and seek immediate medical attention from medical doctor or an optometrist. SKIN: Flush affected spill area with copious amounts of water until the slick sensation to the skin is removed. Wash contaminated clothing before re-wearing. INGESTION: DO NOT Induce Vomiting. Consume as much water as possible. Do not substitute fruit juice or a carbonated beverage for water. Seek medical attention of a physician should be sought. INHALATION: Remove to fresh air. If breathing is difficult, immediate medical attention has to be sought.

\*\*\*\*\*

REACTIVITY DATA

STABILITY (THERMAL, LIGHT, ETC): Stable. INCOMPATIBILITIES (MATERIALS TO AVOID): Strong acidic solutions and oxidizing compounds. HAZARDOUS DECOMPOSITION PRODUCTS: Reaction with various food sugars may form carbon monoxide. Thermal decomposition will also generate carbon monoxide and carbon dioxide. POLYMERIZATION: Will not occur. CONDITIONS TO AVOID: Contact above mentioned substances.

\*\*\*\*\*

SPILL, LEAK AND DISPOSAL PROCEDURES

ACTIONS TO TAKE FOR SPILLS OR LEAKS: Wear protective clothing including rubber gloves, rubber boots, and a supplied air respirator if in a confined area, always wear eye protection. For small spills or drips, dilute with plenty of water and flush to sewer. For large spills, contain by dicing with soil or other absorbent material and then pump into DOT approved waste containers. Comply with all applicable governmental regulations on spill reporting, and handling and disposal of waste. DISPOSAL METHODS: Dispose of contaminated product and materials used for cleaning up spills or leaks in a manner approved for this material. Consult appropriate federal, state and local regulatory agencies to ascertain proper waste disposal procedures.

\*\*\*\*\*

SPECIAL PRECAUTIONS

HANDLING AND STORAGE PRECAUTIONS: Store in cool dry place away from incompatible materials. Protect from freezing. Wash thoroughly after use. Do not get in eyes, on skin, or on clothing. OTHER PRECAUTIONS: Containers, even those that have been emptied, will retain product residue and vapors. Always obey hazard warnings and handle empty containers as if they were full. Do not take internally.

\*\*\*\*\*

FOR ADDITIONAL INFORMATION, CONTACT: Technical Director, Sunbelt Laboratories, during business hours, central time; (281) 261-4747.

\*\*\*\*\*

\*\*\*\*\* MATERIAL SAFETY DATA SHEET \*\*\*\*\*

**"WOOD GLO "**

***Premium Wood Floor Cleaner***